

3. Recommended yarn application



Binder	EUROPE														AMERICAS						
	T61C				T6				T8				T30		TD22	T17	T6M	T18M	T30M	T32M	TD52M
	Fil. Ø	9	102	11	13	34	9	11	5	68	9	6	9	6	9	6	9	7	8	9	
	Tex range	136	204	340	272	408	544	5,5	11	136	204	272	34	66	134	34	68	134	45	11	
Bobbin type	H8	H8	H8	H8	H8	H8	H8	H3	H6	H5/H8	H8	H8	H5	H5	H5	H5/H8	H5	H6	H6	H6	
Construction																					
Veil reinforcement																					
Dry wall tapes																					
Roofing, membrane reinf., facing																					
Facade cladding (EIFS)																					
Flooring																					
Coated fabrics																					
Decorative fabrics																					
Sports and leisure goods																					
Industrial																					
Thermal industrial insulation																					
Air filtration																					
Aluminium filtration																					
PTFE & Silicon Rubber coated fabrics																					
Grinding and cutting wheels																					
Anti corrosion																					
Paper reinforcement																					
Adhesive tapes																					
Medical Casting																					
Other composites																					
Transportation																					
Aircraft																					
Rubber reinforcement																					
Clutch discs, brake linings																					
Marine																					
Electrical																					
Braiding, covering, sleeving																					
Electrical insulation (Tape fabric)																					
Cable reinforcement																					
Electronic																					
PCB's single and double sided																					
PCB's multi layers																					