

E-Glass Products



STORAGE

The material should be stored in its original packaging in dry conditions away from direct sunbeam. Storage temperatures of between 10 and 35 °C (50 and 95 °F) and a relative humidity of between 40 and 70% are recommended.



SHELF LIFE

Though there are no known storage limitations under proper conditions, we recommend to use the material within 6 months after delivery date, or within 24 months after date of manufacture. Retesting is advised after 2 years from initial manufacture date to insure optimum performance. In order to reduce the influence of storage conditions, VETROTEX recommends a First-in-First-out procedure on stocked material (*)



PROCESSING CONDITIONS

Before processing, the material should be conditioned by exposing it to the processing climate for 24 hours.



STACKING INFORMATION

In order to avoid any potential injury or damage, we recommend to limit stacking of our Fiberglass yarn pallets to two (2) in transport, and three (3) in storage areas. For other products in different packaging like e.g. beamed yarn, ZeroTwist, Texturized or Volumized yarn, as well as Textile chopped strands please follow the indicated recommendations.

(*) Storage & Handling Instructions are valid only for products with residual moisture lower than 1%.

Saint-Gobain Vetrotex

Sokolovská 106
57001 Litomyšl
Czech Republic
www.vetrotextextiles.com

Europe

Phone: +420 461 651 495
E-mail: vetrotex@saint-gobain.com

America/Asia/Australia

Phone: +52 246 128 9135
E-mail: vetrotex@saint-gobain.com